

## Erratum

### The frequency control of laser diodes

M. de Labachellerie, C. Latrasse, P. Kemssu and P. Cerez

*J. Phys. III France* 2 (1992) 1557-1589

I) On the bottom of page 1576 and on the top of page 1577, instead of reading the sentences:

“Some appropriate rotation points have been demonstrated experimentally, ( $R_1$  [96] or  $R_2$  [99]), however, we have recently determined rigorously the optimal rotation axis position which should be located on the straight line ( $R_1 R_2$ ) to suppress mode hopping to the first order, the best point being  $R_4$  which can provide a theoretical tuning range broader than 30 nm free of mode hops around 1.5  $\mu\text{m}$  [100].”

replace them by:

“Some appropriate rotation points have been demonstrated experimentally,  $R_1$  [96] or  $R_2$  [99]. We have recently calculated that the best rotation point is effectively  $R_2$ . This point can provide a theoretical tuning range broader than 30 nm free of mode hops around 1.5  $\mu\text{m}$  [100].”

II) On the bottom of page 1576, the previous figure 16 and its caption have to be replaced by the following one:




Fig. 16. — Particular rotation axes:  $R_1$ , suggested in [96];  $R_2$ , suggested in [99];  $R_2$  found with our model in [100].

Commission paritaire N° 57920

---

© Les Editions de Physique 1993

*Directrice de la Publication* : Jeanne BERGER

---

*Short Communications* : saisie, composition **MATHOR3-TEX**  
*Other Communications* : saisie **MATHOR**, composition **PHOTOMAT**  
Impression JOUVE, 18, rue Saint-Denis, 75001 PARIS  
N° 211586Z. Dépôt légal : Août 1993